



Compact Wi-Fi mono laser printer, with small footprint, for easy networking anywhere.

The i-SENSYS LBP151dw is a fast, compact, PCL-ready, Wi-Fi and mobile-enabled black and white laser printer that's affordably priced and ideal for a wide range of uses.



- Fast: 27 ppm output, first print out in 8 seconds, with automatic two-sided printing and Canon Quick First-Print technologies
- Stylish, neat and compact design
- PCL5e/6 optimised printing for compatibility with existing infrastructure
- Wi-Fi and ethernet network-enabled
- Mobile-ready and Google Cloud Print enabled
- Low power consumption and class-leading energy efficiency.



PRINT



Wi-Fi

PRINTER ENGINE

Print speed	Single sided: Up to 27 ppm (A4) Double sided: Up to 15 ipm (A4)
Printing method	Monochrome laser beam printing
Print quality	Up to 1200 x 1200 dpi
Print resolution	Up to 600 x 600 dpi
Warm-up time	Approx. 15 seconds or less from power on
First Page Out Time	Approx. 8 seconds
Recommended Monthly Print Volume	500 - 2,000 pages per month
Duty cycle	Max. 15,000 pages per month ¹
Print margins	5 mm-top, bottom, left and right
Advanced printing features	Google Cloud Print Ready iOS: Canon PRINT Business app Android; Mopria certified, Canon Print Service Plug-in, Canon PRINT Business app

MEDIA HANDLING

Paper input (Standard)	250-sheet cassette 1-sheet multi-purpose tray
Paper output	100-sheet face down, 1 sheet face up
Media types	Plain paper, Recycled Paper, Heavy Paper, Label, Envelope, Transparecy
Media sizes	Cassette (Standard and optional) A4, B5, A5, LGL, LTR, EXECUTIVE, STATEMENT, FOOLSCAP, 16K, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, AFLS, Envelop: COM10, Monarch, C5, DL Custom sizes (Width: 76.2 to 216 mm Length: 210 to 356 mm) Multi-purpose tray: A4, B5, A5, LGL, LTR, EXECUTIVE, STATEMENT, FOOLSCAP, 16K, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, AFLS, Envelop: COM10, Monarch, C5, DL Custom sizes (Width: 76.2 to 216 mm Length: 127 to 356 mm)
Media weights	Cassette: 60 to 163 g/m ² Multi-purpose tray: 60 to 163 g/m ²
Double sided printing	Automatic (A4/LTR/LGL/OFFICIO/B-OFFICIO/ M-OFFICIO/FLS, 60 to 105 g/m ²)

GENERAL FEATURES

Power requirements	220-240V (±10%) 50/60Hz (±2Hz)
Power consumption	Maximum: Approx. 1120W or less Active: Approx. 260W or less Standby: Approx. 2.6W or less Sleep: Approx. 1.1W or less ² Power switch off: 0.5W or less Typical Electricity Consumption (TEC): 0.7kWh/week Idle time required to enter sleep mode: 1-30 min (default: 1 min) Idle time required to enter Auto Shutdown: 4 hours (default)

Noise level

Sound power²
Active: 66 dB or less
Standby: Inaudible

Sound pressure³
Active: 52 dB
Standby: Inaudible

Dimensions (W x D x H)

390 mm x 365 mm x 245 mm

Weight

Approx. 8.6 kg

Operating environment

Temperature: 10 to 30°C (50 to 86°F)
Humidity 20 to 80% RH (no condensation)

Control panel

5 LED indicators, 4 operation keys

CONTROLLER

Processor Speed

400MHz

Memory

512MB

Printer Languages

UFRII (Ultra Fast Rendering), PCL5e, PCL6

Fonts

45 PCL fonts

Interface and connectivity

USB 2.0 High-Speed, 10BASE-T/100 BASE-TX, Wireless
802.11b/g/n

Software and Printer Management

Remote User Interface (RUI),
SSID Tool,
Toner Status Tool,
iW Management Console: Server-based software for
centralised management of a fleet of devices

Operating Systems Compatibility

Windows® 10 / Windows® 8.1 / Windows® 8 / Windows® 7 /
Server® Vista / Server® 2012R2 / Server® 2012 / Server®
2008R2 / Server® 2008 / Server® 2003R2 / Server® 2003
Mac OS X version 10.5.8 & up
Linux®/Citrix

CONSUMABLES

All-in-One cartridges

Standard: Cartridge 737 (2,400 pages)⁵

Footnotes

^[1] Duty cycle is defined as the maximum number of printed pages for a single peak month.
Any usage above the recommended duty cycle may decrease the life of the product

^[2] Wireless: Approx. 1.8 W or less

^[3] Declared noise emission in accordance with ISO 9296

^[4] Web distribution only. Driver will be available in May, 2016.

^[5] Based on ISO/IEC 19752

^[6] Printer ships with 1,700 pages starter cartridge